



Custodian

Project Color and Project Information

FLG-SIERRA DEL MAR

October 27, 2016

Products are available at:
Lake Worth-lantana #2529
10101 Lantana Rd
Lake Worth, FL 33449 5475
(561) 432-1213

Presented by:
SERGIO CESARIO
(561) 400-4346
swrep6344@sherwin.com



Areas Detail

	Description: Resilience® Exterior Acrylic Latex Satin Extra White	Product: K43W00051	Substrate: Stucco	Area: Main Body
	Color: SW6106 - Kilim Beige	Label: Finish	Order #: OE0104869A2529	

Due to screen and print limitations, colors seen here may not accurately reflect painted colors. To confirm your color choices, visit your neighborhood Sherwin-Williams store

	Description: Resilience® Exterior Acrylic Latex Satin Extra White	Product: K43W00051	Substrate: Wood	Area: Trim
	Color: SW7676 - Paper Lantern	Label: Finish	Order #: OE0104869A2529	

Due to screen and print limitations, colors seen here may not accurately reflect painted colors. To confirm your color choices, visit your neighborhood Sherwin-Williams store

	Description: Resilience® Exterior Acrylic Latex Gloss Extra White	Product: K44W00051	Substrate: Aluminum	Area: Garage Door & Front Door
	Color: SW6106 - Kilim Beige	Label: Finish	Order #: OE0104869A2529	

Due to screen and print limitations, colors seen here may not accurately reflect painted colors. To confirm your color choices, visit your neighborhood Sherwin-Williams store

	Description: Resilience® Exterior Acrylic Latex Satin Extra White	Product: K43W00051	Substrate: Stucco	Area: Scheme 1 Accent Color
	Color: SW6164 - Svelte Sage	Label: Finish	Order #: OE0104869A2529	

Due to screen and print limitations, colors seen here may not accurately reflect painted colors. To confirm your color choices, visit your neighborhood Sherwin-Williams store



Areas Detail



Description:
Resilience® Exterior
Acrylic Latex Satin Deep
Base

Product:
K43W00053

Substrate:
Stucco

Area:
Scheme 2 Accent Color

Color:
SW6354 - Armagnac

Label:
Finish

Order #:
OE0104869A2529

Due to screen and print limitations, colors seen here may not accurately reflect painted colors. To confirm your color choices, visit your neighborhood Sherwin-Williams store



Description:
Resilience® Exterior
Acrylic Latex Satin Deep
Base

Product:
K43W00053

Substrate:
Stucco

Area:
Scheme 3 Accent Color

Color:
SW6388 - Golden Fleece

Label:
Finish

Order #:
OE0104869A2529

Due to screen and print limitations, colors seen here may not accurately reflect painted colors. To confirm your color choices, visit your neighborhood Sherwin-Williams store

Custodian

Project Color and Project Information



Reference Pages

Data Pages



**SHERWIN
WILLIAMS.**

102.18

RESILIENCE[®]
Exterior Latex
Satin
K43 Series

As of 4/12/2016, Complies with:			
OTC	Yes	LEED [®] 09 NC CI	N/A
SCAQMD	Yes	LEED [®] 09 CS	N/A
CARB	Yes	LEED [®] 09 H	N/A
CARB SCM 2007	Yes	LEED [®] v4 Emissions	N/A
MPI	Yes	LEED [®] v4 VOC	Yes

CHARACTERISTICS

Resilience Exterior is a high quality exterior finish with MoistureGuard™ Technology for excellent early moisture resistance. This product, which has improved resistance to early dirt pick up, is recommended for use on aluminum and vinyl siding, wood siding, clapboard, shakes, shingles, plywood, masonry, and metal down to a surface and air temperature of 35°F.

VinylSafe™ Color Technology allows the use of many darker colors on vinyl siding that cannot be made in most other coatings.

Color: Most colors
To optimize hide and color development, always use the recommended P-Shade primer

Coverage: 350 - 400 sq ft/gal
@ 4 mils wet; 1.6 mils dry

Drying Time, @ 50% RH:
@ 35-45°F @ 45°F +
Touch: 2 hour 2 hours
Recoat: 24-48 hours 4 hours

Drying and recoat times are temperature, humidity, and film thickness dependent

Flash Point: N/A

Finish: 10-20 units @ 60°

Tinting with CCE:

Base	oz/gal	Strength
Extra White	0-6	Sher-Color
Deep Base	4-12	Sher-Color
Ultra Deep	4-12	Sher-Color
Light Yellow	0-12	Sher-Color
Primary Red	0-12	Sher-Color
Vivid Yellow	0-12	Sher-Color

Vehicle Type: 100% Acrylic

K43W00051

VOC (less exempt solvents):
<50 g/L; <0.42 lb/gal

As per 40 CFR 59.406 and SOR/2009-264, s.12

Volume Solids: 39 ± 2%

Weight Solids: 52 ± 2%

Weight per Gallon: 10.59 lb

Water Vapor Permeance

Based on ASTM D 1653 22.0 perms

Mildew Resistant

This coating contains agents which inhibit the growth of mildew on the surface of this coating film.

SPECIFICATIONS

Aluminum & Aluminum Siding¹
2 cts. Resilience Exterior Latex
Concrete Block, CMU, Split face Block

1 ct. Loxon Block Surfacers
2 cts. Resilience Exterior Latex
Brick

1 ct. Loxon Conditioner²
2 cts. Resilience Exterior Latex

Cement Composition Siding/Panels

1 ct. Loxon Concrete & Masonry Primer/Sealer²

or Loxon Conditioner²
2 cts. Resilience Exterior Latex

Galvanized Steel¹

2 cts. Resilience Exterior Latex

Stucco, Cement, Concrete

1 ct. Loxon Concrete & Masonry Primer/Sealer²

2 cts. Resilience Exterior Latex
Plywood

1 ct. Exterior Latex Wood Primer

2 cts. Resilience Exterior Latex
Steel¹

1 ct. All Surface Enamel Primer²

2 cts. Resilience Exterior Latex

Vinyl Siding

2 cts. Resilience Exterior Latex

Wood, Composition Board

1 ct. Exterior Oil-Based Wood Primer

2 cts. Resilience Exterior Latex

¹ On large expanses of metal siding, the air, surface, and material temperatures must be 50°F or higher.

² Not for use at temperatures under 50° F. See specific primer label for that product's application conditions.

Other primers may be appropriate.

When repainting involves a drastic color change, a coat of primer will improve the hiding performance of the topcoat color.

SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at **1-800-424-LEAD** (in US) or contact your local health authority.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or checked paint to a sound surface. Sand glossy surfaces dull. Seal stains from water, smoke, ink, pencil, grease, etc. with the appropriate primer/sealer. Recognize that any surface preparation short of total removal of the old coating may compromise the service length of the system.

Aluminum and Galvanized Steel

Wash to remove any oil, grease, or other surface contamination. All corrosion must be removed with sandpaper, wire brush, or other abrading method.

Cement Composition Siding/Panels

Remove all dirt, dust, grease, oil, loose particles, laitance, foreign material, and peeling or defective coatings. Allow the surface to dry thoroughly. If the surface is new, test it for pH, if the pH is higher than 8, prime with Loxon Concrete & Masonry Primer/Sealer.

Caulking

Gaps between windows, doors, trim, and other through-wall openings can be filled with the appropriate caulk after priming the surface.



RESILIENCE[®]

Exterior Latex Satin K43 Series

<u>SURFACE PREPARATION</u>	<u>SURFACE PREPARATION</u>	<u>CAUTIONS</u>
<p>Masonry, Concrete, Cement, Block All new surfaces must be cured according to the supplier's recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces should be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with Loxon Concrete & Masonry Primer/Sealer. Cracks, voids, and other holes should be repaired with an elastomeric patch or sealant.</p> <p>Steel Rust and mill scale must be removed using sandpaper, steel wool, or other abrading method. Bare steel must be primed the same day as cleaned.</p> <p>Stucco Remove any loose stucco, efflorescence, or laitance. Allow new stucco to cure at least 30 days before painting. If painting cannot wait 30 days, allow the surface to dry 7 days and prime with Loxon Concrete & Masonry Primer/Sealer. Repair cracks, voids, and other holes with an elastomeric patch or sealant.</p> <p>Vinyl Clean the surface thoroughly by scrubbing with warm, soapy water. Rinse thoroughly, primer with appropriate primer. Do not paint vinyl with any color darker than the original color unless the paint system features VinylSafe™ Color Technology. Painting with darker colors that are not VinylSafe™ may cause vinyl to warp. Follow all painting guidelines of the vinyl manufacturer when painting. Deviating from the manufacturer's painting guidelines may cause the warranty to be voided.</p> <p>Wood, Plywood, Composition Board Clean the surface thoroughly then sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth. All patched areas must be primed. Knots and some woods, such as redwood and cedar, contain a high amount of tannin, a colored wood extract. If applied to these bare woods, it may show some staining. If staining persists, spot prime severe areas with 1 coat of Exterior Oil-Based Wood Primer prior to using.</p>	<p>Mildew Prior to attempting to remove mildew, it is always recommended to test any cleaner on a small, inconspicuous area prior to use. Bleach and bleaching type cleaners may damage or discolor existing paint films. Bleach alternative cleaning solutions may be advised. Mildew may be removed before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.</p> <p style="text-align: center;"><u>APPLICATION</u></p> <p>When the air temperature is at 35°F, substrates may be colder; prior to painting, check to be sure the air, surface, and material temperature are above 35°F and at least 5°F above the dew point. Avoid using if rain or snow is expected within 1-1½ hours. Do not apply at air or surface temperatures below 35°F or when air or surface temperatures may drop below 35°F within 48 hours. No reduction necessary.</p> <p>Brush - Use a nylon/polyester brush. Roller - Use a 3/8" - 3/4" nap synthetic cover. Spray—Airless Pressure.....2000 psi Tip......015"-.019"</p> <p style="text-align: center;"><u>CLEANUP INFORMATION</u></p> <p>Clean spills, spatters, hands and tools immediately with soap and warm water. After cleaning, flush spray equipment with compliant clean up solvent to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using solvents. Do not pour unused contents down the drain. Consult with local authorities for method of disposal and recycling.</p>	<p>For exterior use only. Protect from freezing. Non-photochemically reactive.</p> <p>Before using, carefully read CAUTIONS on label.</p> <p>HOTW 04/12/2016 K43W00051 29 39 Viet, FRC, SP, KOR</p> <p>The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative or visit www.paintdocs.com to obtain the most current version of the PDS and/or an SDS.</p>



**SHERWIN
WILLIAMS.**

102.24

RESILIENCE[®]
Exterior Latex
Gloss
K44 Series

As of 4/13/2016, Complies with:			
OTC	Yes	LEED [®] 09 NC CI	N/A
SCAQM	Yes	LEED [®] 09 CS	N/A
CARB	Yes	LEED [®] 09 H	N/A
CARB SCM 2007	Yes	LEED [®] v4 Emissions	N/A
MPI		LEED [®] v4 VOC	Yes

<u>CHARACTERISTICS</u>	<u>SPECIFICATIONS</u>	<u>SURFACE PREPARATION</u>																					
<p>Resilience Exterior is a high quality exterior finish with MoistureGuard™ Technology for excellent early moisture resistance. This product, which has improved resistance to early dirt pick up, is recommended for use on aluminum and vinyl siding, wood siding, clapboard, shakes, shingles, plywood, masonry, and metal down to a surface and air temperature of 35°F.</p> <p>VinylSafe™ Color Technology allows the use of many darker colors on vinyl siding that cannot be made in most other coatings.</p> <p>Color: Most colors To optimize hide and color development, always use the recommended P-Shade primer</p> <p>Coverage: 350 - 400 sq ft/gal @ 4 mils wet; 1.6 mils dry</p> <p>Drying Time, @ 50% RH: @ 35-45°F @ 45°F + Touch: 2 hour 2 hours Recoat: 24-48 hours 4 hours</p> <p>Drying and recoat times are temperature, humidity, and film thickness dependent</p> <p>Flash Point: N/A</p> <p>Finish: 35-45 units @ 60°</p> <p>Tinting with CCE:</p> <table border="1"> <thead> <tr> <th>Base</th> <th>oz/gal</th> <th>Strength</th> </tr> </thead> <tbody> <tr> <td>Extra White</td> <td>0-6</td> <td>Sher-Color</td> </tr> <tr> <td>Deep Base</td> <td>4-12</td> <td>Sher-Color</td> </tr> <tr> <td>Ultradeep</td> <td>4-12</td> <td>Sher-Color</td> </tr> <tr> <td>Light Yellow</td> <td>0-12</td> <td>Sher-Color</td> </tr> <tr> <td>Primary Red</td> <td>0-12</td> <td>Sher-Color</td> </tr> <tr> <td>Vivid Yellow</td> <td>0-12</td> <td>Sher-Color</td> </tr> </tbody> </table> <p>Vehicle Type: 100% Acrylic K44W00051</p> <p>VOC (less exempt solvents): <50 g/L; <0.42 lb/gal As per 40 CFR 59.406 and SOR/2009-264, s.12</p> <p>Volume Solids: 39 ± 2%</p> <p>Weight Solids: 50 ± 2%</p> <p>Weight per Gallon: 10.10 lb</p> <p>Water Vapor Permeance Based on ASTM D 1653 16.3 perms</p> <p>Mildew Resistant This coating contains agents which inhibit the growth of mildew on the surface of this coating film.</p>	Base	oz/gal	Strength	Extra White	0-6	Sher-Color	Deep Base	4-12	Sher-Color	Ultradeep	4-12	Sher-Color	Light Yellow	0-12	Sher-Color	Primary Red	0-12	Sher-Color	Vivid Yellow	0-12	Sher-Color	<p>Aluminum & Aluminum Siding¹ 2 cts. Resilience Exterior Latex Concrete Block, CMU, Split face Block 1 ct. Loxon Block Surfacers 2 cts. Resilience Exterior Latex Brick 1 ct. Loxon Conditioner² 2 cts. Resilience Exterior Latex Cement Composition Siding/Panels 1 ct. Loxon Concrete & Masonry Primer/Sealer² or Loxon Conditioner² 2 cts. Resilience Exterior Latex Galvanized Steel¹ 2 cts. Resilience Exterior Latex Stucco, Cement, Concrete 1 ct. Loxon Concrete & Masonry Primer/Sealer² 2 cts. Resilience Exterior Latex Plywood 1 ct. Exterior Latex Wood Primer 2 cts. Resilience Exterior Latex Steel¹ 1 ct. All Surface Enamel Primer² 2 cts. Resilience Exterior Latex Vinyl Siding 2 cts. Resilience Exterior Latex Wood, Composition Board 1 ct. Exterior Oil-Based Wood Primer 2 cts. Resilience Exterior Latex</p> <p>¹ On large expanses of metal siding, the air, surface, and material temperatures must be 50°F or higher. ² Not for use at temperatures under 50°F. See specific primer label for that product's application conditions.</p> <p>Other primers may be appropriate.</p> <p>When repainting involves a drastic color change, a coat of primer will improve the hiding performance of the topcoat color.</p>	<p>WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.</p> <p>Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or checked paint to a sound surface. Sand glossy surfaces dull. Seal stains from water, smoke, ink, pencil, grease, etc. with the appropriate primer/sealer. Recognize that any surface preparation short of total removal of the old coating may compromise the service length of the system.</p> <p>Aluminum and Galvanized Steel Wash to remove any oil, grease, or other surface contamination. All corrosion must be removed with sandpaper, wire brush, or other abrading method.</p> <p>Cement Composition Siding/Panels Remove all dirt, dust, grease, oil, loose particles, laitance, foreign material, and peeling or defective coatings. Allow the surface to dry thoroughly. If the surface is new, test it for pH, if the pH is higher than 8, prime with Loxon Concrete & Masonry Primer/Sealer.</p> <p>Caulking Gaps between windows, doors, trim, and other through-wall openings can be filled with the appropriate caulk after priming the surface.</p>
Base	oz/gal	Strength																					
Extra White	0-6	Sher-Color																					
Deep Base	4-12	Sher-Color																					
Ultradeep	4-12	Sher-Color																					
Light Yellow	0-12	Sher-Color																					
Primary Red	0-12	Sher-Color																					
Vivid Yellow	0-12	Sher-Color																					



RESILIENCE[®]

Exterior Latex Gloss K44 Series

<u>SURFACE PREPARATION</u>	<u>SURFACE PREPARATION</u>	<u>CAUTIONS</u>
<p>Masonry, Concrete, Cement, Block All new surfaces must be cured according to the supplier's recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with Loxon Concrete & Masonry Primer/Sealer. Cracks, voids, and other holes should be repaired with an elastomeric patch or sealant.</p> <p>Steel Rust and mill scale must be removed using sandpaper, steel wool, or other abrading method. Bare steel must be primed the same day as cleaned.</p> <p>Stucco Remove any loose stucco, efflorescence, or laitance. Allow new stucco to cure at least 30 days before painting. If painting cannot wait 30 days, allow the surface to dry 7 days and prime with Loxon Concrete & Masonry Primer/Sealer. Repair cracks, voids, and other holes with an elastomeric patch or sealant.</p> <p>Vinyl Clean the surface thoroughly by scrubbing with warm, soapy water. Rinse thoroughly, primer with appropriate primer. Do not paint vinyl with any color darker than the original color unless the paint system features VinylSafe™ Color Technology. Painting with darker colors that are not VinylSafe™ may cause vinyl to warp. Follow all painting guidelines of the vinyl manufacturer when painting. Deviating from the manufacturer's painting guidelines may cause the warranty to be voided.</p> <p>Wood, Plywood, Composition Board Clean the surface thoroughly then sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth. All patched areas must be primed. Knots and some woods, such as redwood and cedar, contain a high amount of tannin, a colored wood extract. If applied to these bare woods, it may show some staining. If staining persists, spot prime severe areas with 1 coat of Exterior Oil-Based Wood Primer prior to using.</p>	<p>Mildew- Prior to attempting to remove mildew, it is always recommended to test any cleaner on a small, inconspicuous area prior to use. Bleach and bleaching type cleaners may damage or discolor existing paint films. Bleach alternative cleaning solutions may be advised. Mildew may be removed before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.</p> <p style="text-align: center;"><u>APPLICATION</u></p> <p>When the air temperature is at 35°F, substrates may be colder; prior to painting, check to be sure the air, surface, and material temperature are above 35°F and at least 5°F above the dew point. Avoid using if rain or snow is expected within 1-1½ hours. Do not apply at air or surface temperatures below 35°F or when air or surface temperatures may drop below 35°F within 48 hours.</p> <p>No reduction necessary.</p> <p>Brush - Use a nylon/polyester brush. Roller - Use a 3/8" - 3/4" nap synthetic cover. Spray—Airless Pressure..... 2000 psi Tip..... .015"-.017"</p> <p style="text-align: center;"><u>CLEANUP INFORMATION</u></p> <p>Clean spills, spatters, hands and tools immediately with soap and warm water. After cleaning, flush spray equipment with compliant clean up solvent to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using solvents. Do not pour unused contents down the drain. Consult with local authorities for method of disposal and recycling.</p>	<p>For exterior use only. Protect from freezing. Non-photochemically reactive.</p> <p>Before using, carefully read CAUTIONS on label.</p> <p>HOTW 04/12/2016 K44W00051 25 30 Viet, FRC,SP, KOR</p> <p>The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative or visit www.paintdocs.com to obtain the most current version of the PDS and/or an SDS.</p>



**SHERWIN
WILLIAMS.**

102.18

RESILIENCE[®]
Exterior Latex
Satin
K43 Series

As of 4/12/2016, Complies with:			
OTC	Yes	LEED [®] 09 NC CI	N/A
SCAQMD	Yes	LEED [®] 09 CS	N/A
CARB	Yes	LEED [®] 09 H	N/A
CARB SCM 2007	Yes	LEED [®] v4 Emissions	N/A
MPI	Yes	LEED [®] v4 VOC	Yes

CHARACTERISTICS

Resilience Exterior is a high quality exterior finish with MoistureGuard™ Technology for excellent early moisture resistance. This product, which has improved resistance to early dirt pick up, is recommended for use on aluminum and vinyl siding, wood siding, clapboard, shakes, shingles, plywood, masonry, and metal down to a surface and air temperature of 35°F.

VinylSafe™ Color Technology allows the use of many darker colors on vinyl siding that cannot be made in most other coatings.

Color: Most colors
To optimize hide and color development, always use the recommended P-Shade primer

Coverage: 350 - 400 sq ft/gal
@ 4 mils wet; 1.6 mils dry

Drying Time, @ 50% RH:
@ 35-45°F @ 45°F +
Touch: 2 hour 2 hours
Recoat: 24-48 hours 4 hours

Drying and recoat times are temperature, humidity, and film thickness dependent

Flash Point: N/A

Finish: 10-20 units @ 60°

Tinting with CCE:

Base	oz/gal	Strength
Extra White	0-6	Sher-Color
Deep Base	4-12	Sher-Color
Ultra Deep	4-12	Sher-Color
Light Yellow	0-12	Sher-Color
Primary Red	0-12	Sher-Color
Vivid Yellow	0-12	Sher-Color

Vehicle Type: 100% Acrylic

K43W00051

VOC (less exempt solvents):
<50 g/L; <0.42 lb/gal

As per 40 CFR 59.406 and SOR/2009-264, s.12

Volume Solids: 39 ± 2%

Weight Solids: 52 ± 2%

Weight per Gallon: 10.59 lb

Water Vapor Permeance

Based on ASTM D 1653 22.0 perms

Mildew Resistant

This coating contains agents which inhibit the growth of mildew on the surface of this coating film.

SPECIFICATIONS

Aluminum & Aluminum Siding¹
2 cts. Resilience Exterior Latex
Concrete Block, CMU, Split face Block

1 ct. Loxon Block Surfacers
2 cts. Resilience Exterior Latex
Brick

1 ct. Loxon Conditioner²
2 cts. Resilience Exterior Latex

Cement Composition Siding/Panels
1 ct. Loxon Concrete & Masonry Primer/Sealer²

or Loxon Conditioner²
2 cts. Resilience Exterior Latex

Galvanized Steel¹
2 cts. Resilience Exterior Latex

Stucco, Cement, Concrete
1 ct. Loxon Concrete & Masonry Primer/Sealer²

2 cts. Resilience Exterior Latex
Plywood

1 ct. Exterior Latex Wood Primer
2 cts. Resilience Exterior Latex

Steel¹
1 ct. All Surface Enamel Primer²

2 cts. Resilience Exterior Latex
Vinyl Siding

2 cts. Resilience Exterior Latex
Wood, Composition Board

1 ct. Exterior Oil-Based Wood Primer
2 cts. Resilience Exterior Latex

¹ On large expanses of metal siding, the air, surface, and material temperatures must be 50°F or higher.

² Not for use at temperatures under 50° F. See specific primer label for that product's application conditions.

Other primers may be appropriate.

When repainting involves a drastic color change, a coat of primer will improve the hiding performance of the topcoat color.

SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at **1-800-424-LEAD** (in US) or contact your local health authority.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or checked paint to a sound surface. Sand glossy surfaces dull. Seal stains from water, smoke, ink, pencil, grease, etc. with the appropriate primer/sealer. Recognize that any surface preparation short of total removal of the old coating may compromise the service length of the system.

Aluminum and Galvanized Steel
Wash to remove any oil, grease, or other surface contamination. All corrosion must be removed with sandpaper, wire brush, or other abrading method.

Cement Composition Siding/Panels
Remove all dirt, dust, grease, oil, loose particles, laitance, foreign material, and peeling or defective coatings. Allow the surface to dry thoroughly. If the surface is new, test it for pH, if the pH is higher than 8, prime with Loxon Concrete & Masonry Primer/Sealer.

Caulking
Gaps between windows, doors, trim, and other through-wall openings can be filled with the appropriate caulk after priming the surface.



RESILIENCE[®]

Exterior Latex Satin K43 Series

<u>SURFACE PREPARATION</u>	<u>SURFACE PREPARATION</u>	<u>CAUTIONS</u>
<p>Masonry, Concrete, Cement, Block All new surfaces must be cured according to the supplier's recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces should be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with Loxon Concrete & Masonry Primer/Sealer. Cracks, voids, and other holes should be repaired with an elastomeric patch or sealant.</p> <p>Steel Rust and mill scale must be removed using sandpaper, steel wool, or other abrading method. Bare steel must be primed the same day as cleaned.</p> <p>Stucco Remove any loose stucco, efflorescence, or laitance. Allow new stucco to cure at least 30 days before painting. If painting cannot wait 30 days, allow the surface to dry 7 days and prime with Loxon Concrete & Masonry Primer/Sealer. Repair cracks, voids, and other holes with an elastomeric patch or sealant.</p> <p>Vinyl Clean the surface thoroughly by scrubbing with warm, soapy water. Rinse thoroughly, primer with appropriate primer. Do not paint vinyl with any color darker than the original color unless the paint system features VinylSafe™ Color Technology. Painting with darker colors that are not VinylSafe™ may cause vinyl to warp. Follow all painting guidelines of the vinyl manufacturer when painting. Deviating from the manufacturer's painting guidelines may cause the warranty to be voided.</p> <p>Wood, Plywood, Composition Board Clean the surface thoroughly then sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth. All patched areas must be primed. Knots and some woods, such as redwood and cedar, contain a high amount of tannin, a colored wood extract. If applied to these bare woods, it may show some staining. If staining persists, spot prime severe areas with 1 coat of Exterior Oil-Based Wood Primer prior to using.</p>	<p>Mildew Prior to attempting to remove mildew, it is always recommended to test any cleaner on a small, inconspicuous area prior to use. Bleach and bleaching type cleaners may damage or discolor existing paint films. Bleach alternative cleaning solutions may be advised. Mildew may be removed before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.</p> <p style="text-align: center;"><u>APPLICATION</u></p> <p>When the air temperature is at 35°F, substrates may be colder; prior to painting, check to be sure the air, surface, and material temperature are above 35°F and at least 5°F above the dew point. Avoid using if rain or snow is expected within 1-1½ hours. Do not apply at air or surface temperatures below 35°F or when air or surface temperatures may drop below 35°F within 48 hours. No reduction necessary.</p> <p>Brush - Use a nylon/polyester brush. Roller - Use a 3/8" - 3/4" nap synthetic cover. Spray—Airless Pressure.....2000 psi Tip......015"-.019"</p> <p style="text-align: center;"><u>CLEANUP INFORMATION</u></p> <p>Clean spills, spatters, hands and tools immediately with soap and warm water. After cleaning, flush spray equipment with compliant clean up solvent to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using solvents. Do not pour unused contents down the drain. Consult with local authorities for method of disposal and recycling.</p>	<p>For exterior use only. Protect from freezing. Non-photochemically reactive.</p> <p>Before using, carefully read CAUTIONS on label.</p> <p>HOTW 04/12/2016 K43W00051 29 39 Viet, FRC, SP, KOR</p> <p>The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative or visit www.paintdocs.com to obtain the most current version of the PDS and/or an SDS.</p>